

Swd Rheinol ATF DSG

High Performance ATF for Double Clutch Transmission (DCT)

Description

Swd Rheinol ATF DSG is a high performance automatic transmission fluid, which was developed for the latest generation of Double Clutch Transmission.

Application

Swd Rheinol ATF DSG is recommended for Audi- and VW-Double Clutch Transmission (DSG), that the ATF oil with No. TL 521 82 and TL 525 29 needs.

Properties

Swd Rheinol ATF DSG provides

- extremely high wear resistance
- high thermal stability
- excellent viscosity-temperature behavior
- low pour point
- foamless, even under difficult conditions
- high oxidation stability
- high load-carrying capacity
- optimum friction characteristics
- Neutral to metals and sealing materials

Specification

Audi / Volkswagen / Seat / Skoda - G 052 182 A2/A6 (TL 52 182), G 052 529 A2/A6 (TL 52 529)
- G 055 529 (TL 52 529-C)

BMW - DCTF-1 (83 220 440 214), MTF-LT-5 (83 22 2167 666), 83 22 0397 244, 83 22 2147 477
83 22 2 148 578, 83 22 2 148 579 and 83 22 2 446 673

Bugatti Veyron

Citroen / Peugeot- 6DCT451 (PSA 9734.S2)

Chrysler Powershift 6-Speed (Getrag), 68044345 EA & GA

Ferrari - TF DCT-F3

Ford/Nissan Powershift 6-Speed (GFT), Ford - WSS-M2C-936-A, WSS-M2C-200-D2

Mercedes Benz - MB 236.25, MB 236.21, MB 236.24

Mitsubishi - Diamond Queen SSTF-1, TC-SST 6-Speed (GFT)

Renault EDC 6-Speed (Getrag)

Porsche - 043 207 29, 043 207 30, 000 043 20, 000 043 305 13, 999 917 080 00

Porsche - 000 043 210 44, 971 094 307 02A

Renault - BOT 450

Volvo Powershift 6-Speed (GFT)/1161838/1161839

ZF TE-ML 11 (ZF004743)

Typical Properties

Swd Rheinol ATF DSG	unit	value	method
Density at 15°C	kg/m³	847	DIN 51 757
Viscosity at 40°C	mm²/s	36	DIN 51 562
Viscosity at 100°C	mm²/s	7	DIN 51 562
Viscosity index		158	DIN ISO 2909
Dynamic Viscosity at -40°C	mPa.s	< 18.000	DIN 51 938
Pourpoint	°C	-45	DIN ISO 3016
Flash point COC	°C	> 200	DIN ISO 2592

Article-Number : **30633**

Specification variations in these characteristics may occur.
The instructions of manufacturer must be regarded.
Further informations to be available by MSDS.

Swd Lubricants GmbH & Co. KG
Am Schlütershof 26
D-47059 Duisburg
Tel.: 0203 / 31919-0
Fax: 0203 / 3191998