



Swd Rheinol ATF DX III H

AUTOMATIC TRANSMISSION FLUID

Description

Swd Rheinol ATF DX III H - fluid is an Automatic Transmission Fluid, which is made from mineral base oils and products from the synthesis technology, in combination with a special additive package.

Application

Swd Rheinol ATF DX III H is used in automatic vehicle gears, servo steerings, fluid couplings and hydrodynamic converters as well as in hydraulics of passenger cars, commercial vehicles, busses and construction vehicles, if an ATF of Dexron III H - type is recommended.

Properties

Swd Rheinol ATF DX III H affords following benefits :

- Optimally balanced frictional behaviour
- Very good wear protection
- Excellent cold fluidity
- Outstanding oxidation stability
- Good corrosion- and rust preventive properties
- Low foaming tendency and best elastomer compatibility

Specification / Recommendations

- | | |
|----------------------------------|--|
| ❖ DEXRON III H und Dexron III G | ❖ Ford Mercon |
| ❖ Allison C-4 | ❖ Ford M2C138-CJ, M2C 166-H |
| ❖ Allison TES, 389 | ❖ Volvo 97340, 97341 |
| ❖ MB 236.1, 236.5, 236.6 & 236.7 | ❖ Voith 55.6335 & 55.6336 |
| ❖ MAN 339 Typ Z1 & V1, Z2 & V2 | ❖ ZF TE-ML 02F, 04D, 09,11A, 14A & 17C |

Typical Values

Swd Rheinol ATF DX III H	unit	value	method
Density at 15	kg/m ³	851	DIN 51 757
Viscosity at 40°C	mm ² /s	40	DIN 51 562
Viscosity at 100°C	mm ² /s	8,1	DIN 51 562
Viscosity Index		182	DIN ISO 2909
Pourpoint	°C	-50	DIN ISO 3016
Flash Point	°C	220	DIN ISO 2592

Article-Number : 32836

Specification variations in these characteristics may occur.
The instructions of manufacturer must be regarded.
Further informations to be available by MSDS.

Swd Lubricants GmbH & Co. KG
Am Schlütershof 26
D-47059 Duisburg
Tel.: 0203 / 3191940
Fax: 0203 / 3466540