

Swd Rheinol ATF - TASA

AUTOMATIC TRANSMISSION FLUID

Description and Application

Swd Rheinol ATF - TASA is an Automatic Transmission Fluid for the use in automatic gears and torque converters, if a gear oil is recommended, which meets the specifications described below. It is also used in manual transmissions, load change gears, power steerings and hydraulics of motor cars.

Swd Rheinol ATF - TASA is produced from highly refined base stocks. Approved additives provide a performance level, which features a very low pour point, a very high viscosity index and a good shear stability. It prevents deposits and protects the gear against corrosion. Its foaming tendency is very low, it provides best oxidation stability and a good compatibility with elastomers.

Specification / Recommendations

- ❖ GM ATF Type A, Suffix A
- ❖ MB 236.2
- ❖ Renk (Doromat)
- ❖ MAN 339 Typ A

Typical Values

Swd Rheinol ATF - TASA	unit	value	method
Density at 15	kg/m ³	854	DIN 51 757
Viscosity at 40°C	mm ² /s	37,8	DIN 51 562
Viscosity at 100°C	mm ² /s	8,2	DIN 51 562
Viscosity Index		200	DIN ISO 2909
Pourpoint	°C	-45	DIN ISO 3016
Flash Point	°C	219	DIN ISO 2592

Article-Number : 32811

Specification variations in these characteristics may occur.
The instructions of manufacturer must be regarded.
Further informations to be available by MSDS.

Swd Lubricants GmbH & Co. KG
Am Schlütershof 26
D-47059 Duisburg
Tel.: 0203 / 31919-0
Fax: 0203 / 3191999