

Swd Rheinol Antifreeze GW 11

-40°C

Antifreeze Readymix for Motor Vehicles

Description and Application

Swd Rheinol Antifreeze GW 11 (-40°C) is a ready water-diluted antifreeze based on ethylenglycole. It is free of amines, nitrites and phosphates. The special inhibitor-package protects outstandingly the engine and the cooling circuit against frost, rust and excessive heat. It is also applicable for light metal motors.

Swd Rheinol Antifreeze GW 11 (-40°C) is pre-diluted by demineralized water. It may be used undiluted or be further diluted by normal tap water. The minimum concentration, in order to assure a sufficient corrosion protection, should not go below 50%. This is especially regarded at summer operation.

It is recommended to change the antifreeze at least after 5 years operating time.

If the engine constructor specifies the use of a product free of silicate, the respective operation instruction has to be regarded (VW, Audi, Seat, Skoda, Ford, GM/Opel from 1997).

Specification / Recommendations

- ◆ MB 325.0 & 325.2
- ◆ BMW GS 94000
- ◆ MAN 324 NF
- ◆ Cummins 85T8
- ◆ Volvo 128
- ◆ VW / Audi / Seat / Skoda / Porsche TL 774-C (G11)
- ◆ Opel GME L301
- ◆ Saab 6901 599
- ◆ Lada TTM VAZ 1.97.717-97
- ◆ Ford ESD-M97B94-A
- ◆ MTU MTL 5048

Technical Properties

Swd Rheinol Antifreeze GW 11 -40°C	unit	value
Density at 20°C	kg/m³	1084
Colour		blau
Pour Point	°C	-40
Flash Point	°C	>100
pH		8,4
Boiling Point	°C	>145
Warensorten-Nummer :		39120

Specification variations in these characteristics may occur.
The instructions of manufacturer must be regarded.
Further informations to be available by MSDS.

Swd Lubricants GmbH & Co. KG
Am Schlütershof 26
D-47059 Duisburg
Tel.: 0203 / 31919-0
Fax: 0203 / 3191999