



Swd Rheinol Antifreeze GW 13

-40°C

Modern Antifreeze Readymix for Motor Vehicles

Description and Application

Swd Rheinol Antifreeze GW 13 - (-40°C) is a ready water-diluted modern antifreeze based on ethylenglycole, to be used for motor vehicles with engines of cast iron, aluminum and / or from the combination of both metals.

Swd Rheinol Antifreeze GW 13 - (-40°C) is particularly recommended for light metal engines where a special aluminum protection is required at higher temperatures.

Swd Rheinol Antifreeze GW 13 (-40°C)

- provides long lasting protection due to the combination of the organic inhibitors
- forms a homogeneous protective layer due to the sophisticated additive package
- offers thanks to highly effective additives to protect all metals, including aluminum
- is environmentally friendly, being free of nitrite, amine, phosphate and borate-

Specifications / Recommendations

Audi / Seat / Skoda / VW - TL774J (G13)

Typical Values

Swd Rheinol Antifreeze GW 13 -40°C	unit	value
Density at 20°C	kg/m³	1080
Colour		pink
Pour Point	°C	-40
Flash Point	°C	>100
pH		8,6
Boiling Point	°C	>100

Article-Number : 39160

Specification variations in these characteristics may occur.
The instructions of manufacturer must be regarded.
Further informations to be available by MSDS.

Swd Lubricants GmbH & Co. KG
Am Schlütershof 26
D-47059 Duisburg
Tel.: 0203 / 31919-0
Fax: 0203 / 3191999