

Swd Rheinol EXPERT XH SAE 10W-40

HIGH PERFORMANCE OIL FOR EURO-4 and EURO-5 COMMERCIAL CAR ENGINES

Product Description

Swd Rheinol EXPERT XH 10W-40 is a high performance engine oil, which is made from base oils of the most modern synthesis technology. It is suitable for each kind of diesel engines in commercial cars, especially for EURO 4- and - 5- motors (EURO 4 &-5 does only limited apply to MAN and DAF).

Swd Rheinol EXPERT XH 10W-40 assures top performance in many quality criterions :

- Easy low-wear cold-start by good fluidity, even at low temperatures.
- Excellent aging and corrosion protection.
- Exceeding wear protection and cleaning power.
- Allows the most extended oil drain intervals which car producers recommend.
- Outstanding thermal oxydative stability and low evaporation tendency.
- High performance additives and the synthetic base care for unexcelled performance.

Specification / Recommendation

ACEA E4 / E7Scania LDF-2API CI-4 / SLCaterpillar ECF 1-a, ECF 2Renault RXDGlobal DHD-1Deutz DQC IV-10Mack EO-M+MTU Typ 3Detroit Diesel 93K215Cummins CES 20076, 20077, 20078DAF HP

Approval

MB-approval 228.5 MAN M 3277 MAN M 3377 VOLVO VDS-3 Mack EO-N Renault VI RLD-2

Typical Proporties

| Swd Rheinol EXPERT XH SAE 10W-40 | unit | value | method |
|----------------------------------|---------------|-------|--------------|
| Density at 15°C | kg/m³ | 868 | DIN 51 757 |
| Viscosity at 40°C | mm²/s | 98,1 | DIN 51 562 |
| Viscosity at 100°C | mm²/s | 14,5 | DIN 51 562 |
| Viscosity Index | | 152 | DIN ISO 2909 |
| CCS at -25°C | mPa.s | 6580 | ASTM D5293 |
| Pourpoint | °C | -36 | DIN ISO 3016 |
| Flashpoint | °C | 224 | DIN IS0 2592 |
| TBN | mg KOH/g | 12,8 | DIN ISO 3771 |
| | Article-No. : | 31011 | |

Fax: 0203 / 3191999