



# Swd Rheinol Fouke 4T

## SAE 10W40

## High Performance Multigrade Oil for Motorcycles

### Description and Properties

**Swd Rheinol Fouke 4T 10W40** is a high performance special engine oil for motor cycles with air- and water-cooled 4-stroke engines of highest output.

It is the ideal partner for all sportive motor-cycles, on all roads and off-road.

The high capacity is assured by a combination of high quality base oils with successfully tested additives.

**Swd Rheinol Fouke 4T 10W40** offers

- optimal lubrication in motor and in gear and assured functionality of wet clutches. even at extreme operation conditions and continuous use.
- outstanding motor cleanliness, especially at pistons and valves.
- good cold-starting properties.

### Specifications / Recommendations

ACEA A3

API SN

JASO MA2

### Typical Properties

Swd Rheinol Fouke 4T SAE 10W40	unit	value	method
Density at 15°C	kg/m <sup>3</sup>	863	DIN 51 757
Viscosity at 40°C	mm <sup>2</sup> /s	97,5	DIN 51 562
Viscosity at 100°C	mm <sup>2</sup> /s	15,1	DIN 51 562
Viscosity Index		161	DIN ISO 2909
Dynam. Viscos.at -25°C	mPa.s	5590	DIN 51 377
Pourpoint	°C	-39	DIN ISO 3016
Flash point	°C	232	DIN ISO 2592
TBN	mg KOH/g	10,5	DIN ISO 3771

**Article-Number : 32340**

Specification variations in these characteristics may occur.  
The instructions of manufacturer must be regarded.  
Further informations to be available by MSDS.

**Swd Lubricants GmbH & Co. KG**  
Am Schlütershof 26  
D-47059 Duisburg  
Tel.: 0203 / 31919-0  
Fax: 0203 / 3191998