



Swd Rheinol Fouke 4T

SAE 10W50

High Performance Multigrade Oil for Motorcycles

Properties

Swd Rheinol Fouke 4T 10W50 is a high performance special engine oil for motor cycles with air- and water-cooled 4-stroke engines of highest output. It is the ideal partner for all sportive motor-cycles, on all roads and off-road.

The high capacity is assured by a combination of high quality base oils with successfully tested additives.

Swd Rheinol Fouke 4T 10W50 offers

- optimal lubrication in motor and in gear and assured functionality of wet clutches even at extreme operation conditions and continuous use.
- outstanding motor cleanliness, especially at pistons and valves.
- highest wear protection of all power transmission components in motor and gear.
- good cold-starting and low friction properties.
- all-seasons use at temperate climate

Specification / Recommendations

ACEA A3-04
API SN
JASO MA2

Typical Values

Swd Rheinol Fouke 4T SAE 10W50	unit	value	method
Density at 15°C	kg/m ³	866	DIN 51 757
Viscosity at 40°C	mm ² /s	117	DIN 51 562
Viscosity at 100°C	mm ² /s	17,6	DIN 51 562
Viscosity Index		166	DIN ISO 2909
Dynam. Viscos.at -25°C	mPa.s	6900	DIN 51 377
Pourpoint	°C	-36	DIN ISO 3016
Flash point	°C	226	DIN ISO 2592
TBN	mg KOH/g	10,5	DIN ISO 3771

Article-Number : 32350

Specification variations in these characteristics may occur.
The instructions of manufacturer must be regarded.
Further informations to be available by MSDS.

Swd Lubricants GmbH & Co. KG
Am Schlütershof 26
D-47059 Duisburg
Tel.: 0203 / 3191940
Fax: 0203 / 3466540