



# Swd Rheinol Fouke 4T

## SAE 15W-50

## High Performance Multigrade Oil for Motorcycles

### Properties

**Swd Rheinol Fouke 4T 15W50** is a high performance special engine oil for motor cycles with air- and water-cooled 4-stroke engines of highest output.

It is the ideal partner for all sportive motor-cycles, on all roads and off-road.

The high capacity is assured by a combination of high quality base oils with successfully tested additives.

**Swd Rheinol Fouke 4T 15W50** offers

- optimal lubrication in motor and in gear and assured functionality of wet clutches even at extreme operation conditions and continuous use.
- outstanding motor cleanliness, especially at pistons and valves.
- highest wear protection of all power transmission components in motor and gear.
- all-seasons use at temperate climate

### Specification / Recommendations

ACEA A3-04

API SN

JASO MA2

### Typical Values

Swd Rheinol Fouke 4T SAE 15W-50	unit	value	method
Density at 15°C	kg/m <sup>3</sup>	872	DIN 51 757
Viscosity at 40°C	mm <sup>2</sup> /s	138	DIN 51 562
Viscosity at 100°C	mm <sup>2</sup> /s	19,1	DIN 51 562
Viscosity Index		157	DIN ISO 2909
Dynam. Viscos.at -20°C	mPa.s	5740	DIN 51 377
Pourpoint	°C	-36	DIN ISO 3016
Flash point	°C	226	DIN ISO 2592
TBN	mg KOH/g	10,5	DIN ISO 3771

**Article-Number :** 32347

Specification variations in these characteristics may occur.  
The instructions of manufacturer must be regarded.  
Further informations to be available by MSDS.

**Swd Lubricants GmbH & Co. KG**  
Am Schlütershof 26  
D-47059 Duisburg  
Tel.: 0203 / 3191940  
Fax: 0203 / 3466540