



Swd Rheinol Fouke 4T

SAE 20W-50

High Performance Multigrade Oil for Motorcycles

Properties

Swd Rheinol Fouke 4T 20W50 is a high performance special engine oil for motor cycles with air- and water-cooled 4-stroke engines of highest output.

It is the ideal partner for all sportive motor-cycles, on all roads and off-road.

The high capacity is assured by a combination of high quality base oils with successfully tested additives.

Swd Rheinol Fouke 4T 20W50 offers

- optimal lubrication in motor and in gear and assured functionality of wet clutches even at extreme operation conditions and continuous use.
- outstanding motor cleanliness, especially at pistons and valves.
- highest wear protection of all power transmission components in motor and gear.

Specification / Recommendations

ACEA A3-04

API SN

JASO MA2

Typical Values

Swd Rheinol Fouke 4T SAE 20W-50	unit	value	method
Density at 15°C	kg/m ³	891	DIN 51 757
Viscosity at 40°C	mm ² /s	153	DIN 51 562
Viscosity at 100°C	mm ² /s	18,3	DIN 51 562
Viscosity Index		133	DIN ISO 2909
Dynam. Viscos.at -25°C	mPa.s	6980	DIN 51 377
Pourpoint	°C	-27	DIN ISO 3016
Flash point	°C	228	DIN ISO 2592
TBN	mg KOH/g	10,5	DIN ISO 3771

Article-Number :

32320

Specification variations in these characteristics may occur.

The instructions of manufacturer must be regarded.
Further informations to be available by MSDS.

Rheinischer Schmierstoffvertrieb GmbH
Am Schlütershof 28
D-47059 Duisburg
Tel.: 0203 / 318760
Fax: 0203 / 3187614