



Swd Rheinol Primus FOS

SAE 5W-30

High Performance Fuel Economy Oil for Passenger Cars

Description and Properties

Swd Rheinol PRIMUS FOS SAE 5W-30 is a high-alloyed all-seasons oil for those passenger car engines, which require fuel economy (FE) oils. Low viscosity of special base oils coming from the synthesis-technology provides by fast oil circulation and low frictional resistance noticeable reduction of fuel consumption and pollutant emission.

Swd Rheinol PRIMUS FOS SAE 5W-30 is equal to all thermal and mechanical loads, which may occur in modern fuel economy passenger car engines.

- high cleaning-and dirt holding capacity (Detergent/Dispersant) provide excellent motor cleanliness.
- outstanding fuel economy properties by special friction reducing additives.
- cost-effective all-seasons oil with noticeable fuel reduction.
- takes care for the environment by reduced emissions of CO₂ and particles.

Specifications / Recommendations

ACEA A5 / B5

API SL

FORD WSS-M2C 913-B / C / D

Renault RN 0700

Jaguar / Land Rover STJLR.03.5003

Typical Values

Swd Rheinol Primus FOS SAE 5W-30	unit	value	method
Density at 15°C	kg/m ³	848	DIN 51 757
Viscosity at 40°C	mm ² /s	55,0	DIN 51 562
Viscosity at 100°C	mm ² /s	9,9	DIN 51 562
Viscosity Index		176	DIN ISO 2909
CCS at -30°C	mPa.s	3410	DIN 51 377
Pourpoint	°C	-42	DIN ISO 3016
Flashpoint	°C	230	DIN ISO 2592
TBN	mg KOH/g	9,5	DIN ISO 3771

Article-No. : 31173

Specification variations in these characteristics may occur.
The instructions of manufacturer must be regarded.
Further informations to be available by MSDS.

Swd Lubricants GmbH & Co. KG
Am Schlütershof 26
D-47059 Duisburg
Phone: 0203 / 31919-0
Fax: 0203 / 3191999