



Swd Rheinol Primus GM

SAE 5W-30

Innovative High Performance Low Friction Engine Oil

Description

Swd Rheinol Primus GM SAE 5W-30 is a modern multigrade low friction engine oil of the latest generation for all-seasons use. The combination of unconventional hydrocrack base oils with the most modern additive technology assures a low viscous, shear-stable motor oil, which safely prevents deposits, lowers frictional losses of the motor and optimally protects against wear. This leads to fuel economy and concurrently to extended motor life.

Application

Swd Rheinol Primus GM SAE 5W-30 is specially recommended for OPEL - gasoline and diesel engines, turbo charger and catalytic converter included. Constructor regulations to be regarded.

Specification :

ACEA A3/B4-04	Opel GM-LL-A-025
API SL / CF	Opel GM-LL-B-025

Typical Values

Swd Rheinol Primus GM SAE 5W-30	unit	value	method
Density at 15 °C	kg/m ³	855	DIN 51 757
Viscosity at 40 °C	mm ² /s	66,00	DIN 51 562
Viscosity at 100 °C	mm ² /s	11,73	DIN 51 562
Viscosity Index		175	DIN ISO 2909
Dynamamic viscosity at -30 °C	mPa.s	5850	DIN 51 377
Pourpoint	°C	-48	DIN ISO 3016
Flash Point	°C	226	DIN ISO 2592
Article-Number :		31225	

Specification variations in these characteristics may occur.
The instructions of manufacturer must be regarded.
Further informations to be available by MSDS.

Swd Lubricants GmbH & Co. KG
Am Schlütershof 26
D-47059 Duisburg
Tel.: 0203 / 3191940
Fax: 0203 / 3466540