



Swd Rheinol Synkrol 4 MX

SAE 75W-80

Semisynthetic Standard Transmission Oil

Description and Properties

Swd Rheinol Synkrol 4 MX - SAE 75W80 is made from high quality HC-synthetic base oils. In combination with a modern additive-package there is achieved a performance level which has to be described as follows:

- Excellent high pressure- and wear protection properties
- Very good properties in corrosion- and rust protection
- Low foaming tendency and excellent aging stability
- High viscosity index and low pour point care for easy gear changing even at lot temperatures
- Reduced oil consumption and extended oil drain intervals

Application

Swd Rheinol Synkrol 4 MX - SAE 75W80 is used for the lubrication of synchronized and non-synchronized standard transmissions. Especially it is recommended for commercial vehicles, which are furnished with BMW, VW and Mercedes Benz manual transmissions.

Specification / Recommendation

- | | |
|------------------------------|-----------------------------------|
| ❖ API GL-4 | ❖ VW G052 512, G052 178, G052 527 |
| ❖ BMW MTF LT-1/-2/-3/-4 | ❖ VW G052 532, G052 171, G052 726 |
| ❖ FORD WSS-M2C200-D2 | ❖ VW G055 726, G052 725, G060 726 |
| ❖ MB 235.10 | ❖ VW G 009 317 |
| ❖ PSA B 71 2330 / 9730 A2/A8 | ❖ Toyota JWS 227 |
| ❖ Volvo 97308 / 97309 | ❖ Special Honda MTF/MTF-II |

Typical Properties

Swd Rheinol Synkrol 4 MX SAE 75W-80	unit	value	method
SAE - Classification		75W-80	
Density at 15°C	kg/m³	855	DIN 51 757
Viscosity at 40°C	mm²/s	51,2	DIN 51 562
Viscosity at 100°C	mm²/s	9,1	DIN 51 562
Viscosity Index		161	DIN ISO 2909
Pourpoint	°C	-42	DIN ISO 3016
Flash point	°C	215	DIN ISO 2592

Article-No. :	32517
----------------------	--------------

Specification variations in these characteristics may occur.
The instructions of manufacturer must be regarded.
Further informations to be available by MSDS.

Swd Lubricants GmbH & Co. KG
Am Schlütershof 26
D-47059 Duisburg
Phone: 0203 / 3191940
Fax: 0203 / 3466540