



Swd Rheinol Twoke Synmix Ultra

Synthetic High Performance 2-Stroke Oil

Description and Properties

Swd Rheinol Twoke Synmix Ultra is a fully synthetic 2-stroke motor oil to be used in air- and water-cooled road and racing engines. Its capacity exceeds the actually most stringent specification requirements of all 2-stroke motor manufacturers.

Swd Rheinol Twoke Synmix Ultra is produced from high-temperature proof and most lubricious synthetic base oils and special low-ash additives of latest technology, which assure

- optimal motor lubrication even under high-speed racing conditions
- reduction of deposits in the combustion chamber, at the sparking plugs, in the circular grooves and the exhaust system
- improved pollution control by scentless and smokeless combustion
- universal use in all lubrication systems (fresh oil lubrication, auto-lube systems, mixed lubrication) and for all gasoline fuels

Swd Rheinol Twoke Synmix Ultra was designed for the use in high-speed racing engines of motor cycles and carts as well as for normal sports engines or for 2-stroke engines, which require disproportionately high lubrication guarantee.

Specifications / Recommendations

API TC
ISO - L - EGD
JASO FD
TISI

Typical Properties

Swd Rheinol Twoke Synmix Ultra	unit	value	method
Density at 15°C	kg/m³	886	DIN 51 757
Color		green	visual
Viscosity at 40°C	mm²/s	63,30	DIN 51 562
Viscosity at 100°C	mm²/s	7,6	DIN 51 562
Viscosity index		101	DIN ISO 2909
Pourpoint	°C	-52	DIN ISO 3016
Flash point	°C	172	DIN ISO 2592
Sulphated ash	% mass.	0,10	DIN 51 575

Article-No. : 32160

Specification variations in these characteristics may occur.
The instructions of manufacturer must be regarded.
Further informations to be available by MSDS.

Swd Lubricants GmbH & Co. KG
Am Schlütershof 26
D-47059 Duisburg
Phone: 0203 / 31919-0
Fax: 0203 / 3191999