

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 26.05.2015

*

*

Version number 2

Revision: 26.05.2015

SECTION 1: Identification	
	of the substance/mixture and of the company/undertaking
· 1.1 Product identifier	
• Trade name: Fouke 4T SAE 20V	V-50
 Article number: 32320 1.2 Relevant identified uses of the No further relevant information a Application of the substance / the Multigrade Motor Oil for Motorcy SAE 20W-50 	e mixture
• 1.3 Details of the supplier of the • Manufacturer/Supplier: SWD Lubricants GmbH & Co.KG Am Schlütershof 26 D-47059 Duisburg Tel : 0049 (0)203 31919-0 Fax : 0049 (0)203 31919-99 E-mail:info@swd-gmbh.de	
 Further information obtainable j Department product safety sdb@swd-gmbh.de 1.4 Emergency telephone numbe Informationszentrale gegen Vergi 	
SECTION 2: Hazards ident • 2.1 Classification of the substanc • Classification according to Regu The product is not classified acco	ce or mixture lation (EC) No 1272/2008
• Classification according to Direct • Information concerning particult The product does not have to be guideline for preparations of the Contact with skin and inhalation	c tive 67/548/EEC or Directive 1999/45/EC Not applicable. Fa r hazards for human and environment: I abelled due to the calculation procedure of the "General Classificatio
• Classification system: The classification is according to data.	the latest editions of the EU-lists, and extended by company and literatur
The classification is according to	
The classification is according to data. • 2.2 Label elements • Labelling according to Regulatio • Hazard pictograms Void • Signal word Void • Hazard statements Void • 2.3 Other hazards • Results of PBT and vPvB assesses • PBT: Not applicable.	on (EC) No 1272/2008 Void nent



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 26.05.2015

Version number 2

Revision: 26.05.2015

Trade name: Fouke 4T SAE 20W-50

	(Conto	l. of page 1)
· Dangerous compone	ents:	
	Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts Xi R38-41; N R51/53 Eye Dam. 1, H318; Aquatic Chronic 2, H411; Skin Irrit. 2, H315	<i>≤</i> 2.5%
	Calciumalkyl-Phenat-Sulfid,langkettig R53 Aquatic Chronic 4, H413	≤ 2.5%

· SVHC Void

• Additional information: For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

• 4.1 Description of first aid measures

- General information: Take affected persons out of danger area and lay down.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray.

Use fire extinguishing methods suitable to surrounding conditions.

• For safety reasons unsuitable extinguishing agents: Water with full jet

- · 5.2 Special hazards arising from the substance or mixture
- In case of fire, the following can be released: carbondioxide
- · 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.
- · Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Keep people at a distance and stay on the windward side.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- 6.4 Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

SECTION 7: Handling and storage

• 7.1 Precautions for safe handling Avoid the formation of oil haze.

(Contd. on page 3)

Swd Identication High quality oils made in germany

Printing date 26.05.2015

Safety data sheet according to 1907/2006/EC, Article 31

Version number 2

Revision: 26.05.2015

(Contd. of page 2)

Trade name: Fouke 4T SAE 20W-50

· Information about fire - and explosion protection: No special measures required.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

• Requirements to be met by storerooms and receptacles:

Note Regulation on facilities for the storage, filling and handling water-polluting substances...

- · Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions: Storage in a collecting room is required.

• 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace: Oilfog and Oilfumes TLV-8h-TWA 5mg/m³

Oilfog and Oilfumes TLV-8h-TWA 5mg/n TLV-15min-STEL 10mg/m³

· Additional information:

The lists valid during the making were used as basis.

Used engine oil may contain considered dangerous combustion products which can cause skin cancer. Any skin contact should be avoided by applying personal hygiene measures. (See Chapter 8)

· 8.2 Exposure controls

- · Personal protective equipment:
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

- · Respiratory protection: Not required.
- Protection of hands:

Preventive skin protection by use of skin-protecting agents is recommended.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · Not suitable are gloves made of the following materials: Leather gloves
- · Eye protection: Goggles recommended during refilling

	ysical and chemical properties	
General Information		
Appearance:	clear	
Form:	Fluid	
Colour:	Brown	
Odour:	Mineral-oil-like	
Odour threshold:	Not determined.	



Printing date 26.05.2015

Safety data sheet according to 1907/2006/EC, Article 31

Version number 2

Revision: 26.05.2015

Trade name: Fouke 4T SAE 20W-50

	(Contd. of page	
pH-value:	Not determined.	
Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	Undetermined.	
Pour point	- 27 °C (DIN ISO 3016)	
Flash point:	228 °C (DIN ISO 2592)	
Flammability (solid, gaseous):	Not applicable.	
Ignition temperature:		
Decomposition temperature:	Not determined.	
Self-igniting:	Not determined.	
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapou	
	mixtures are possible.	
Explosion limits:		
Lower:	0.6 Vol % (DIN EN 1839)	
Upper:	6.5 Vol % (DIN EN 1839)	
Vapour pressure:	Not determined.	
Density at 20 °C:	0.888 g/cm ³ (DIN 51757)	
Relative density	Not determined.	
Vapour density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
water:	Not miscible or difficult to mix.	
Partition coefficient (n-octanol/wo	ater): Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Organic solvents:	0.0 %	
9.2 Other information	No further relevant information available.	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions Reacts with strong oxidising agents.
- 10.4 Conditions to avoid No further relevant information available.
- \cdot 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity
- · LD/LC50 values relevant for classification:

Rat oral : > 2000 mg/kg (Concawe Product dossier 01/54)

(Contd. on page 5)

GB



Printing date 26.05.2015

Safety data sheet according to 1907/2006/EC, Article 31

Version number 2

Revision: 26.05.2015

Trade name: Fouke 4T SAE 20W-50

(Contd. of page 4)

68649-42-3 Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts

 $Oral \ LD50 > 2000 \ mg/kg \ (rat)$

- · Primary irritant effect:
- · Skin corrosion/irritation Prolonged skin contact it may cause irritations
- · Serious eye damage/irritation No irritating effect.
- · Respiratory or skin sensitisation No sensitising effects known.
- · Additional toxicological information:

The product is not subject to classification according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version.

When used and handled according to specifications, the product does not have any harmful effects to our experience and the information provided to us.

Used engine oil may contain considered dangerous combustion products which can cause skin cancer. Any skin contact should be avoided by applying personal hygiene measures. (See Chapter 8)

· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

The product contains less than 3% DMSO extract (method IP346). A classification as a carcinogen with R45 is deleted. (Note L)

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

The product spreads out on the surface of the water. A small fraction of the constituents will be dissolved. It prevents the solution of oxygen and can cause the death of water organismn.

68649-42-3 Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts

EC50 1 - 1.5 mg/kg (daphnia) (OECD Guide-line 202 part1, Daphnia A.I.T.)

· 12.2 Persistence and degradability Not easily biodegradable

· 12.3 Bioaccumulative potential

Due to the distribution coefficient n-octanol/water a worth-mentioning accumulation in organisms is not expected.

- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- *Remark:* The product can easily be separated by an oil separator (skimmer) of the water surface.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

• *Recommendation* Delivery of waste oil to offically authorised collectors only.

· European waste catalogue

13 02 05* mineral-based non-chlorinated engine, gear and lubricating oils

(Contd. on page 6)



Printing date 26.05.2015

Safety data sheet according to 1907/2006/EC, Article 31

Version number 2

Revision: 26.05.2015

Trade name: Fouke 4T SAE 20W-50

(Contd. of page 5)

· Uncleaned packaging:

· Recommendation:

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

SECTION 14: Transport information

· 14.1 UN-Number · ADR, ADN, IMDG, IATA	Void
· 14.2 UN proper shipping name · ADR, ADN, IMDG, IATA	Void
· 14.3 Transport hazard class(es)	
· ADR, ADN, IMDG, IATA · Class	Void
· 14.4 Packing group · ADR, IMDG, IATA	Void
· 14.5 Environmental hazards: · Marine pollutant:	No
· 14.6 Special precautions for user	Not applicable.
· 14.7 Transport in bulk according to Annex II o MARPOL73/78 and the IBC Code	f Not applicable.
· UN "Model Regulation":	-

SECTION 15: Regulatory information

 \cdot 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Labelling according to Regulation (EC) No 1272/2008 Void

· Hazard pictograms Void

· Signal word Void

· Hazard statements Void

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· National regulations:

• Additional classification according to Decree on Hazardous Materials, Annex II: The product does not have to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

· Information about limitation of use: none

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- *H411 Toxic to aquatic life with long lasting effects.*
- H413 May cause long lasting harmful effects to aquatic life.

(Contd. on page 7)

GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 26.05.2015

Version number 2

Revision: 26.05.2015

Trade name: Fouke 4T SAE 20W-50

	(Contd. of page
R38	Irritating to skin.
R41	Risk of serious damage to eyes.
R51/5	3 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R53	May cause long-term adverse effects in the aquatic environment.
· Denar	tment issuing MSDS: Product safety
	wiations and acronyms:
	Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the Internati
	ge of Dangerous Goods by Road)
	International Maritime Code for Dangerous Goods
	International Air Transport Association
	Slobally Harmonised System of Classification and Labelling of Chemicals
	S: European Inventory of Existing Commercial Chemical Substances
	S: European List of Notified Chemical Substances
CAS: C	hemical Abstracts Service (division of the American Chemical Society)
LC50: 1	Lethal concentration, 50 percent
	Lethal dose, 50 percent
	it. 2: Skin corrosion/irritation, Hazard Category 2
	m. 1: Serious eye damage/eye irritation, Hazard Category 1
	c Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2
	c Chronic 4: Hazardous to the aquatic environment - Chronic Hazard, Category 4
	es Concawe Product Dossier No.97/108. Concawe Product Dossier Nn. 01/54.
· * Date	a compared to the previous version altered.