

Swd Rheinol Primol Power Synth CS

SAE 20W-50

High Performance Low Friction Motor Oil for Passenger Cars

Description and Properties

Swd Rheinol Primol Power Synth CS SAE 20W-50 is a high performance low friction oil to be used in passenger cars gasoline and diesel engines. It is produced by blending high quality synthetic oils and mineral base stocks and additives of most progressive technology.

Suitable also under severe operating conditions in modern passenger car engines, turbo- or non-turbo charged, and for vans , too.

Swd Rheinol Primol Power Synth CS SAE 20W-50 by its optimized formulation provides lowered fuel- and oil consumption. Because of its extended viscosity range the all seasons use is possible.

A special booster raises the quality level up to API SN, which provides improved oxidation resistance, improved deposit protection, better wear protection, and better low-temperature performance over the life of the oil. This leads to an improved motor cleanliness and at least to an extended motor life.

Specifications / Recommendations

ACEA A3/B4

API SP / CF

Typical Properties

Swd Rheinol Primol Power Synth CS SAE 20W-50	unit	value	method
Density at 15°C	kg/m ³	889,8	DIN 51 757
Viscosity at 40°C	mm ² /s	160,6	DIN 51 562
Viscosity at 100°C	mm ² /s	18,0	DIN 51 562
Viscosity Index		124	DIN ISO 2909
CCS at -15°C	mPa.s	7380	DIN 51 377
HTHS-Viscosity at 150°C	mPa.s	min. 3,5	ASTM D5481
Pourpoint	°C	-39	DIN ISO 3016
Flashpoint	°C	214	DIN ISO 2592
TBN	mg KOH/g	10,8	DIN ISO 3771

Article-Number : 31446

Specification variations in these characteristics may occur.
The instructions of manufacturer must be regarded.
Further information to be available by MSDS.

Swd Lubricants GmbH & Co. KG
Am Schlütershof 26
D-47059 Duisburg
Tel.: 0203 / 31919-0
Fax: 0203 / 3191998