

Swd Rheinol PRIMUS CVS

SAE 5W-30



High Performance Low Friction Oil

Description and Properties

Swd Rheinol PRIMUS CVS SAE 5W-30 is a high performance low friction oil, which is designed for gasoline and diesel engines of passenger cars, and which especially can be used for fuel injectec and turbo charged engines.

It is blended from high quality hydrocracked base oils and selected additives. This makes for a lubricant quality which fulfills and exceeds all requirements of modern passenger car engines.

swd PRIMUS CVS SAE 5W-30 has following advantages to be pointed out

- excellent cold start and fast oil feed even at temperatures down to lower than -30°C reduce fuel consumption.
- optimized high temperature viscosity and outstanding low friction properties lower oil-caused emissions.
- high wear and corrosion protection and a very good dispersancy provide for an excellent cleanliness of the engine and for long motor life.
- All seasons use by outstanding temperature-viscosity properties and reliable performance reserves even at long drain intervals.

Specifications / Recommendations

ACEA A3-/ B4

API SL / CF

VW 502 00 / 505 00

MB 229.3

BMW Longlife-01

Renault RN0700 und RN0710

Opel GM-LL-B-025

Approvals

MB Approval 229.5

Typical Properties

Swd Rheinol PRIMUS CVS SAE 5W-30	unit	value	method
Density at 15°C	kg/m ³	853	DIN 51 757
Viscosity at 100°C		11,5	DIN 51 562
Viscosity Index	mPa.s	163	DIN ISO 2909
CCS at -30°C	°C	5850	DIN 51 377
Pourpoint	mPa.s	-42	DIN ISO 3016
Flashpoint	°C	236	DIN ISO 2592
TBN	mg KOH/g	10	DIN ISO 3771

Article-Number : 31178

Specification variations in these characteristics may occur.
The instructions of manufacturer must be regarded.
Further informations to be available by MSDS.

Swd Lubricants GmbH & Co. KG
Am Schlüttershof 26
D-47059 Duisburg
Tel.: 0203 / 31919-0
Fax: 0203 / 3191998