



Swd Rheinol PRIMUS CVS

SAE 5W-40

High Performance Low Friction Oil

Description and Properties

Swd Rheinol PRIMUS CVS SAE 5W-40 is a high performance low friction oil, which is designed for gasoline and diesel engines of passenger cars, and which especially can be used for fuel injected and turbo charged engines.

It is blended from high quality hydrocracked base oils and selected additives. This makes for a lubricant quality which fulfills and exceeds all requirements of modern passenger car engines.

Swd Rheinol PRIMUS CVS SAE 5W-40 has following advantages to be pointed out

- excellent cold start and fast oil feed even at temperatures down to lower than -30°C reduce fuel consumption.
- optimized high temperature viscosity and outstanding low friction properties lower oil-caused emissions.
- high wear and corrosion protection and a very good dispersancy provide for an excellent cleanliness of the engine and for long motor life.
- All seasons use by outstanding temperature-viscosity properties and reliable performance reserves even at long drain intervals.

Specifications / Recommendations

ACEA A3/B4
API SP
BMW Longlife - 01
BMW LL 98
Fiat 9.55535 M2
MB 226.5

Opel GM-LL-B-025
VW 502 00 / 505 00
PSA B71 2296
Renault RN0700 and RN0710
Lamborghini
Maserati

Approvals

MB Approval 229.5*
Porsche A 40

*covers MB 229.3

Typical Properties

Swd Rheinol PRIMUS CVS SAE 5W-40	unit	value	method
Density at 15°C	kg/m ³	853	DIN 51 757
Viscosity at 100°C		14,3	DIN 51 562
Viscosity Index	mPa.s	173	DIN ISO 2909
CCS at -30°C	°C	6260	DIN 51 377
Pourpoint	mPa.s	-39	DIN ISO 3016
Flashpoint	°C	226	DIN ISO 2592
TBN	mg KOH/g	10,6	DIN ISO 3771

Article-Number : 31168

Specification variations in these characteristics may occur.
The instructions of manufacturer must be regarded.
Further information to be available by MSDS.

Swd Lubricants GmbH & Co. KG
Am Schlütershof 26
D-47059 Duisburg
Tel.: 0203 / 31919-0
Fax: 0203 / 3191998