



Swd Rheinol Primus EVR

SAE 15W-50

Semi synthetic high Performance Oil for Passenger Car Engines

Description and Properties

Swd Rheinol Primus EVR 15W50 is a high performance multi grade motor oil for modern gasoline and diesel engines, which make special demands to the motor oil because of their progressive design principles.

Swd Rheinol Primus EVR 15W50 is based on high quality synthetic and mineral oils, which are produced by modern technologies. These, in combination with selected additives for the warranty of motor cleanliness, cleanliness, wear protection and the oxidation stability, make a top product available which meets the requirements of today's high performance engines, running with diesel as well as with gasoline fuel.

Because of the wide range of its viscosity-temperature properties the product is especially recommended for all-season use in warm and in tropical climates.

Specifications / Recommendations

ACEA A3 / B4

API SN / CF

VW 505 00

MB 229.1

PSA B71 2294 und B71 2300

Typical Properties

Swd Rheinol Primus EVR SAE 15W-50	unit	value	method
Density at 15°C	kg/m³	868	DIN 51 757
Viscosity at 40°C	mm²/s	155	DIN 51 562
Viscosity at 100°C	mm²/s	21,1	DIN 51 562
Viscosity Index		161	DIN ISO 2909
CCS at -20°C	mPa.s	4800	DIN 51 377
Pourpoint	°C	-42	DIN ISO 3016
Flashpoint	°C	222	DIN ISO 2592
TBN	mg KOH/g	12,4	DIN ISO 3771

Article-Number : 31128

Specification variations in these characteristics may occur.
The instructions of manufacturer must be regarded.
Further informations to be available by MSDS.

Swd Lubricants GmbH & Co. KG
Am Schlütershof 26
D-47059 Duisburg
Tel.: 0203 / 31919-0
Fax: 0203 / 3191999