



Swd Rheinol Primus Longlife Ultra

SAE 5W-30

Fully Synthetic High Performance Low Friction Oil for Passenger Cars

Description :

Swd Rheinol Primus Longlife Ultra SAE 5W-30 is a modern low friction oil with an advanced performance according to the latest requirements, providing excellent wear protection and above-average cleaning power. It contributes to the service life extension of exhaustaftertreatment systems and redounds to their trouble-free operation.

Properties :

Swd Rheinol Primus Longlife Ultra SAE 5W-30 is produced on base of the highest quality components, which are currently available. The product ist completely compatible with the newest diesel particulate filters (DPF) and with catalytic converters of gasoline engines. It combines outstanding performance with excellent motor protection and improves the reduction of fuel consumption.

Swd Rheinol Primus Longlife Ultra SAE 5W-30 provides

- contribution in the reduction of particle built-up on the diesel particulate filter by its low ash content
- reduction of the danger of poisoning on catalytic converters of gasoline engines by its low sulphur and low phosphorus amounts.
- reduction of deposits and sludge by effective cleaning additives
- extended oil drain intervals, because of decelerated oil aging by outstanding thermic stability
- trouble-free cold-starting behaviour by very good low temperature properties

Application :

Swd Rheinol Primus Longlife Ultra SAE 5W-30 is recommended for all modern motor cars, especially for high power Otto- and diesel engines in the newest models of passenger cars, sports cars and light commercial vehicles.

Specifications / Recommendations

ACEA C3
API SP
Porsche C 30

Approvals :

VW 504 00 / 507 00
MB-Approval 229.51 and MB-Approval 229.52
BMW Longlife-04

Typical Values

Swd Rheinol Primus Longlife Ultra SAE 5W-30	unit	value	method
Density at 15°C	kg/m³	850	DIN 51 757
Viscosity at 40°C	mm²/s	67,1	DIN 51 562
Viscosity at 100°C	mm²/s	11,9	DIN 51 562
Viscosity Index		175	DIN ISO 2909
CCS at -30°C	mPa.s	5140	DIN 51 377
HTHS at 150 °C	mPa.s	3,5	ASTM D4683
Pourpoint	°C	-42	DIN ISO 3016
Flash Point	°C	232	DIN ISO 2592
TBN	mg KOH/g	7,7	DIN ISO 3771

Article-Number : 31183

Specification variations in these characteristics may occur.
The instructions of manufacturer must be regarded.
Further informations to be available by MSDS.

Swd Lubricants GmbH & Co. KG
Am Schlütershof 26
D-47059 Duisburg
Tel.: 0203 / 31919-0
Fax: 0203 / 3191999