



# Swd Rheinol Primus VO

**SAE 0W-20**

Special high-performance engine oil for Volvo Engines

## Description and Properties

**Swd Rheinol Primus VO SAE 0W-20** is a special high-performance engine oil based on synthesis technology. It has been developed specifically for use in Volvo engines.

This special additive-technology ensures an excellent lubrication safety.

Through the combined effect of low viscosity with the specially developed additives high fuel saving is made possible and thus the reduction of CO<sub>2</sub> - emissions. Modern engines make caused by downsizing and modern start-stop systems more and greater demands on the engine oil. These are guaranteed with superior wear characteristics and additional power reserves by the new technology.

The used additive-package has been specially developed for the high demands of the new Volvo VCC RBS0-2AE.

## Specifications / Recommendations

ACEA C5

API SP, SN

VOLVO VCC RBS0-2AE

## Typical Properties

Swd Rheinol Primus VO SAE 0W-20	unit	value	method
Density at 15°C	kg/m <sup>3</sup>	845	DIN 51 757
Viscosity at 40°C	mm <sup>2</sup> /s	48	DIN 51 562
Viscosity at 100°C	mm <sup>2</sup> /s	9,1	DIN 51 562
Viscosity Index		177	DIN ISO 2909
CCS at -35°C	mPa.s	5980	DIN 51 377
Pourpoint	°C	-48	DIN ISO 3016
Flashpoint	°C	236	DIN ISO 2592
Article-No. :		31188	

Specification variations in these characteristics may occur.  
The instructions of manufacturer must be regarded.  
Further informations to be available by MSDS.

**Swd Lubricants GmbH & Co. KG**  
Am Schlütershof 26  
D-47059 Duisburg  
Phone: 0203 / 31919-0  
Fax: 0203 / 3191999